

**XP0101P IP Phone**  
**2-line HD SIP desktop phone with liquid crystal display (LCD)**



	General
Chipset	DSPG
Flash memory	8MB
SRAM memory	32MB
Dimensions (W*D*H*T; handset on cradle, stand attached)	197mm*200mm*158mm*50mm
Weight (handset on cradle,stand attached)	
Temperature	-10~50°C
Humidity	10-95%
Power consumption(approx.)	1.09-3.2W
Connections	
LAN (PC port)	10/100Mb Ethernet
WAN (Internet port)	10/100Mb Ethernet
Adapter	Input : AC 100-240V Output : D
PoE(802.3af) built-in	√

PoE(802.3af) class	Class 2
Handset(RJ-9)	√
Headset(RJ-9)	√
Foot stand	√
Wall mounting	√
Expansion module	×
User interface	
Display type	2.3" 132×64 graphic LCD
LCD Backlight	√
Hard keys in all	39
DSS keys	6
Soft keys	4
Navigation keys	6
Volume key	√
Fixed feature keys	9 (Call/History/Message/Headset/Cor Redial/Handsfree)
Power and ring indicator LED	√
DSS keys with dual color LED	√

Message indicator LED	√
Headset indicator LED	√
External device	
XP0020 Expansion module	x
EHS36 wireless headset adapter	x
YHS32 headset	√
Voice	
HD voice	HD Speaker HD Handset
Wideband codec	G.722
G.711 A-law/μ-law	√
G.726	√
G.723.1	x
G.729AB	√
HAC (Hearing aid compatibility)	√
VAD (Voice activity detection)	√
CNG (Comfort noise generator)	√
AEC (Acoustic echo canceling)	√
PLC (Packet loss concealment)	√

AJB (Adaptive jitter buffer)	√
AGC (Automatic gain control)	√
Side tone	√
Quality of Service(QoS)	802.1p/Q, ToS/DSCP
Telephony features	
SIP Accounts	2
Hands-free speakerphone	Full Duplex
Redial	√
Auto redial	√
Mute	√
3-way conferencing	√
Caller ID display	√
Call hold	√
Call waiting	√
Call transfer(blind/attended)	√
Call forward	√
Call History(all/missed/ received/dialed/forwarded)	100 entries
DND	√

SMS	√
Voice mail	√
Message waiting indicator(MWI)	√
Speed Dial	√
Ringtone selection	√
Volume control	√
Import of individual ringtone	√
Tone setting	√
Local Phonebook	1000 entries
Phonebook import/export	√
Phonebook search	Intelligent search method
Black list	√
Phone lock (keypad lock)	√
LCD display logo	√
# or * key as Send function	√
Hotline	√
Localized language	√
Reset to factory	√

View Voice Mail	√
Headset (Call center mode)	√
Zero-SP-Touch	√
IP PBX and IP Centrex features	
BLF (Busy Lamp field)	√
BLA (Bridged Line Appearance)	√
Paging	√
Intercom	√
Call park	√
Call pickup	√
Call completion	√
Call recording	√
Anonymous call	√
Anonymous call rejection	√
Auto answer	√
Emergency call	√
Call return	√
Group pickup	√

Group listening	√
Distinctive Ringtone	√
Music on hold(via PBX)	√
Music on hold(via sever)	√
Dial Plan	√
PUSH XML	x
Network and Time	
WAN Static IP/DHCP/PPPoE	√
PC port mode	Bridge
DHCP server for PC port	√
SNTP/NTP	√
Setup date and time by manual	√
Daylight saving time	√
IPv6	ICMPv6, Static
DNS Cache	√
VLAN	Autoconfiguration through DHCP/L
Action URL& Action URI	√
Multicast IP Paging	√

Security	
HTTPS (server/client)	√
TLS (Transport Layer Security)	√
SRTP (RFC3711)	√
AES for auto-provision	√
3-level privilege	Admin/VAR/User
Web Interface	
Embedded web server	HTTP/HTTPS
Edit phonebook via web	√
Send SMS via web	√
Dial via web	√
Web logout	√
Management (config/upgrade)	
Configuration via LCD	√
Configuration via web	√
Configuration via autoprovision	√
Automatic firmware update	√
Manual firmware update	√



Auto provisioning via LCD	√
Auto provisioning via Web	TFTP/FTP/HTTP/HTTPS
Auto provisioning with PnP	√
TR-069	√
Redundancy Server	√
SNMP	√
Provisioning redirection (via phone)	√
Package tracing export	√
System log export	√
SIP	
SIP v1 (RFC2543)	√
SIP v2 (RFC3261)	√
UDP/TCP/TLS	√
Out-of-band DTMF(RFC 2833)	√
In-band DTMF	√
SIP INFO DTMF	√
STUN client (NAT traversal)	√
Rport (RFC3581)	√

Digest/basic authentication	Digest (MD5)
Peer-to-peer SIP link mode	√
Loose routing and strict routing support	√
PRACK (RFC3262)	√
Error-information support	√
Reliability of provisional responses (RFC3262)	√
DNS SRV (RFC3263), redundant server support	√
Offer/answer (RFC3264)	√
Message Waiting Indication (RFC3842)	√
Subscription for MWI events (RFC3265)	√
Dialog-state monitoring(RFC 4235)	√
REFER (RFC3515)	√
Event list subscription support (RFC4662)	√
Advanced features	
XML phonebook (Central)	√
XML browser	√
Hot-desking	√
OpenVPN	√

802.1x	√
LDAP phonebook	√
Soft key programmable	√
Broadsoft Advanced Features	
Network Conference	√
Network Call Logs	√
Auto-P synchronization	√
DND & Forward synchronization	√
BLF List	√
Call Forward	√
Call Pickup	√
Call Park	√
Call Center Features	√
Contacts	√
Meet-me conference	√
Alert-Info	√
BroadWorks Anywhere	√
Sequential Ring	√

Simultaneous Ring Personal	√
Anonymous Call	√
Anonymous Call Rejection	√
Remote Office	√
CosmoCom Advanced Features	
ACD	√
Other features	
Certification	CE/FCC
Broadsoft Validated	√
Asterisk/Digium Certificated	√
Packing	
Giftbox size	224mm*236mm*130mm
PCS/CTN	10 PCS
Carton measure	675mm*468mm*250mm
N.W	
G.W	